






























## HI100K-DVR

	Items	Description	User Price	
1	THC-B110-M	1 MP high-performance CMOS, 1280 × 720 resolution, 2.8 mm, 3.6 mm, 6 mm fixed lens, Day/Night switch, EXIR 2.0, smart IR, up to 20 m IR distance, 4 in 1 video output (switchable TVI/AHD/CVI/CVBS), IP66	IRR 4,810,000	
2	THC-B120-P	2 MP high-performance CMOS-1920 × 1080 resolution- 2.8 mm, fixed focal lens-Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance-Switchable TVI/AHD/CVI/CVBS- IP66	IRR 6,500,000	
3	THC-B120-M	2 MP high-performance CMOS-1920 × 1080 resolution- 2.8 mm, fixed focal lens-Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance-Switchable TVI/AHD/CVI/CVBS- IP66- METAL	IRR 7,090,000	
3	THC-B120-MPIRL	2 MP PIR Fixed Mini Bullet Camera 2 MP, 1920 × 1080 resolution, 2.8 mm, 3.6 mm fixed focal lens, Smart IR, up to 20 m IR distance, PIR detection, strobe light alarm IP66	IRR 7,630,000	
	THC-B140-P	4 MP high-performance CMOS-2560 × 1440 resolution- 2.8 mm fixed focal lens-Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- -DWDR-BLC-IP66	IRR 7,240,000	
5	THC-B140-M	4MP high-performance CMOS - 2560 × 1440 resolution- 2.8 mm- fixed focal lens-Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) -DWDR-IP 66-BLC-Full Metal	IRR 7,990,000	
6	THC-B220	2 MP high-performance CMOS-1920 × 1080 resolution- 2.8 mm fixed focal lens-Day/Night switch- EXIR 2.0, smart IR, up to 40 m IR distance-Switchable TVI/AHD/CVI/CVBS-IP66	IRR 7,590,000	
7	THC-B220-M	2MP CMOS Sensor, 40m IR, Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, DWDR- OSD Menu, IP66, 2.8/3.6/6mm Lens, Support HD-TVI/AHD/CVI/CVBS video output-Full Metal	IRR 8,440,000	
8	THC-B240	4MP high-performance CMOS - 2560 × 1440 resolution- 2.8 mm- fixed focal lens-Day/Night switch- EXIR 2.0, smart IR, up to 40 m IR distance- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) -DWDR-BLC-IP 66	IRR 9,110,000	

9	<b>THC-B240-M</b>	4MP CMOS Sensor, EXIR Bullet, <b>40m IR</b> , ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, <b>DNR-DWDR, OSD Menu</b> , IP66, <b>2.8/3.6/6mm Lens</b> ,Support HD-TVI/AHD/CVI/CVBS video output-Full Metal	<b>IRR 9,940,000</b>	
10	<b>THC-T110-P</b>	1 MP high-performance CMOS, 1280 × 720 resolution, 2.8 mm, 3.6 mm, 6 mm fixed focal lens, Day/Night switch, EXIR 2.0, smart IR, up to 20 m IR distance, 4 in 1 video output (switchable TVI/AHD/CVI/CVBS), Switchable TVI/AHD/CVI/CVBS. Pelastic case	<b>IRR 3,460,000</b>	
11	<b>THC-T120-PC</b>	2 MP high-performance CMOS- 1920 × 1080 resolution- <b>2.8 mm</b> , fixed focal lens-Day/Night switch- EXIR 2.0, smart IR, up to <b>20 m IR</b> distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- <b>IP66-DWDR-BLC</b>	<b>IRR 4,900,000</b>	
12	<b>THC-T120</b>	2 MP high-performance CMOS- 1920 × 1080 resolution- <b>2.8 mm</b> , fixed focal lens-Day/Night switch- EXIR 2.0, smart IR, up to <b>20 m IR</b> distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- <b>IP66-DWDR-BLC</b>	<b>IRR 7,400,000</b>	
13	<b>THC-T120-M</b>	2 MP high-performance CMOS- 1920 × 1080 resolution- <b>2.8 mm</b> , fixed focal lens-Day/Night switch- EXIR 2.0, smart IR, up to <b>20 m IR</b> distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- <b>IP66-DWDR-BLC-METAL</b>	<b>IRR 6,270,000</b>	
14	<b>THC-T140-P</b>	4 MP high-performance CMOS-2560 × 1440 resolution- <b>2.8 mm</b> , <b>Fixed</b> focal lens-Day/Night switch-EXIR 2.0, smart IR, up to <b>20 m IR</b> distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS) <b>DWDR-BLC-IP66</b>	<b>IRR 7,340,000</b>	
15	<b>THC-T140</b>	4 MP high-performance CMOS-2560 × 1440 resolution- <b>2.8 mm</b> , Fixed focal lens-Day/Night switch-EXIR 2.0, smart IR, up to <b>20 m IR</b> distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS) <b>DWDR-BLC-IP66</b>	<b>IRR 7,400,000</b>	
16	<b>THC-T140-M</b>	4 MP high-performance CMOS-2560 × 1440 resolution- <b>2.8 mm</b> , Fixed focal lens-Day/Night switch-EXIR 2.0, smart IR, up to <b>20 m IR</b> distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS) <b>DWDR-BLC-IP66-METAL</b>	<b>IRR 8,400,000</b>	
17	<b>THC-T220-P</b>	2 MP high-performance CMOS-1920 × 1080 resolution- <b>2.8 mm</b> ,fixed focal lens-Day/Night switch-EXIR 2.0, smart IR, up to <b>40 m IR</b> distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- <b>IP66-DWDR-BLC</b>	<b>IRR 6,580,000</b>	
18	<b>THC-T220-M</b>	2 MP high-performance CMOS-1920 × 1080 resolution- <b>2.8 mm</b> ,fixed focal lens-Day/Night switch-EXIR 2.0, smart IR, up to <b>40 m IR</b> distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- <b>IP66-DWDR-BLC-METAL</b>	<b>IRR 7,710,000</b>	
19	<b>THC-T240-P</b>	4 MP high-performance CMOS-2560 × 1440 resolution- <b>2.8 mm</b> fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to <b>40 m IR</b> distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- <b>DWDR-BLC-IP66</b>	<b>IRR 8,740,000</b>	
20	<b>THC-T240-M</b>	4 MP high-performance CMOS-2560 × 1440 resolution- <b>2.8 mm</b> fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to <b>40 m IR</b> distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- <b>DWDR-BLC-IP66-METAL</b>	<b>IRR 9,900,000</b>	

21	Vari-Focal Series			
22	<b>THC-B320-VF</b>	2MP CMOS Sensor, <b>40m IR</b> , Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR,, <b>DWDR- DNR, OSD Menu, IP66, 2.8-12mm Vari Focal Lens</b> , Support HD-TVI/AHD/CVI/CVBS video output-Front cover: Metal-Main body: Plastic-Bracket: Metal	<b>IRR 15,200,000</b>	
23	<b>THC-B340-VF</b>	4MP CMOS Sensor - <b>2.8-12mm Vari Focal Lens</b> , EXIR Bullet, <b>40m IR</b> , ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, <b>DNR,DWDR, OSD Menu, IP66</b> , Support HD-TVI/AHD/CVI/CVBS video output-Front cover: Metal-Main body: Plastic-Bracket: Metal	<b>IRR 16,780,000</b>	
24	<b>THC-D320-VF</b>	2MP CMOS Sensor, <b>40m IR</b> , EXIR Dome, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, DWDR-OSD Menu, <b>IP66, 2.8-12mm Vari Focal Lens</b> --support HD-TVI/AHD/CVI/CVBS video output-,IK10-Full Metal	<b>IRR 14,900,000</b>	
25	<b>THC-D340-VF</b>	4MP CMOS Sensor, EXIR Dome, <b>40m IR</b> , ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, <b>DNR,DWDR- OSD Menu, IP66, 2.8-12mm Vari Focal Lens</b> ,IK10, Support HD-TVI/AHD/CVI/CVBS video output-Full Metal	<b>IRR 16,110,000</b>	
26	<b>THC-T320 VF</b>	2MP CMOS Sensor, <b>40m IR</b> , EXIR Eyeball, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, <b>DNR, DWDR-OSD Menu, IP66, 2.8-12mm Vari Focal Lens</b> , Support HD-TVI/AHD/CVI/CVBS video output-Cover&Base:Plastic- Eyeball: Metal	<b>IRR 13,780,000</b>	
27	<b>THC-T340-VF</b>	4MP CMOS Sensor, EXIR Eyeball, <b>40m IR</b> , ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR,DWDR- <b>OSD Menu, IP66, 2.8-12mm Vari Focal Lens</b> , Support HD-TVI/AHD/CVI/CVBS video output-Cover&Base:Plastic-Eyeball: Metal	<b>IRR 15,070,000</b>	
28	Turbo HD PTZ Camera			
29	<b>PTZ-T4225I-D</b>	1/2.8" HD progressive scan CMOS 1920 × 1080 resolution 25× optical zoom, 16× digital zoom 120 dB true WDR (Wide Dynamic Range) Up to 100 m IR distance 3D intelligent positioning SwitchableTVI/AHD/CVI/CVBS video outputs	<b>IRR 71,040,000</b>	
30	<b>PTZ-T4215I-D</b>	1/2.8" HD progressive scan CMOS 1920 × 1080 resolution 15× optical zoom, 16× digital zoom 120 dB true WDR (Wide Dynamic Range) Up to 100 m IR distance 3D intelligent positioning Switchable TVI/AHD/CVI/CVBS video outputs	ناموجود	
31	<b>PTZ-T5225I-A</b>	1/2.8" HD progressive scan CMOS 1920 × 1080 resolution 25× optical zoom DWDR (Digital Wide Dynamic Range) Up to 150 m IR distance 3D intelligent positioning Switchable turbo HD and CVBS outputs	ناموجود	
32	DVR 4 Channel			
33	<b>DVR-104G-F1</b>	4-ch 1080p Mini 1U Lite H.264 DVR,5 signals input adaptively (HDTVI/AHD/CVI/CVBS/IP),Long distance transmission over UTP and coaxial cable,H.265 Pro+ compression to improve encoding efficiency and reduce data storage costsSupports 1080p lite,Encoding ability up to 1080p lite @ 12 fps,One HDD for continuous video recording,Smart search for efficient playback.	<b>IRR 8,830,000</b>	

34	DVR-204G-F1	Recording Capability <b>HD1080p Lite</b> <b>4-ch -HD-TVI/AHD/CVI/CVBS</b> video & 1-ch audio input, - <b>1-ch Up to 960P resolution), 1 SATA (6TB)</b> interface, HD1080p Lite @ 25 fps/ch, 260 1U case-- <b>HDMI output HD1080p-Metal</b>	IRR 11,120,000	
35	DVR-204Q-F1	Recording Capability <b>3MP</b> <b>4-ch -HD-TVI/AHD/CVI/CVBS</b> video & 1-ch audio input, <b>1-ch IP video input(up to HD1080p resolution), 1 SATA(6TB)</b> interface, CH 1: 3MP @ 12 fps, CH 2-4:1920x1080P: 12 fps/ch, 260 1U case-- <b>HDMI outputHD1080p-Metal</b>	IRR 12,370,000	
36	DVR-204Q-K1	H265+ compression saving up to 50% on bandwidth and storage. Recording 2MP@15FPS on 1080P or @25FPS on 1080PLite (3MP@15FPS on channel 1) Support self-adaptive HDTV/HDCVI/AHD/CVBS signal input.Add up to 2 x 6MP IP cameras.HDMI output at 1920 x 1080 resolution Up to 4-ch synchronous playback at 1080p resolution playback at up to 256X speed.	IRR 15,490,000	
37	DVR-204U-F1	Recording Capability <b>5MP/3MP</b> <b>4-ch -HD-TVI/AHD/CVI/CVBS</b> video & 1-ch audio input, - <b>2-ch IP video input(up to 6MP resolution), 1 SATA (6 TB)</b> - interface,5MP@12fps,4MP@15fps,3MP@18fps,1080p/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N), 315 1U case-- <b>HDMI output HD1080p-Metal</b>	IRR 19,020,000	
38	DVR-204U-K1	Self-adaptive HDTV/HDCVI/AHD/CVBS signal input I Up to 8/16-ch 8 MP IP cameras input for DVR-204/208U-K1 I 8 MP/5 MP/4 MP HDTV video input and live view for DVR-208U-K1, and 5MP/4 MP for DVR-204U-K1 I Defogging function enabled for the supported analog cameras I Long distance transmission over UTP and coaxial cable: max. 800m for 1080p and 1200m for 720p HDTV signal	IRR 22,170,000	
39	<b>DVR 8 Channel</b>			
40	DVR-108G-F1	8-ch 1080p Mini 1U Lite H.264 DVR, 5 signals input adaptively (HDTV/AHD/CVI/CVBS/IP),Long distance transmission over UTP and coaxial cable,H.265 Pro+ compression to improve encoding efficiency and reduce data storage costsSupports 1080p lite,Encoding ability up to 1080p lite @ 12 fps,One HDD for continuous video recording,Smart search for efficient playback.	IRR 15,050,000	
41	DVR-208G-F1	Recording Capability <b>HD1080p Lite</b> <b>8-ch -HD-TVI/AHD/CVI/CVBS</b> video & 1-ch audio input, - <b>2-ch Up to 960P resolution), 1 SATA(6TB)</b> interface, HD1080p Lite @ 12 fps/ch, 260 1U case-- <b>HDMI output HD1080p-Metal</b>	IRR 18,380,000	
42	DVR-208Q-F1	Recording Capability <b>3MP</b> <b>8-ch -HD-TVI/AHD/CVI/CVBS</b> video & 1-ch audio input, - <b>2-ch IP video input(up to HD1080p resolution), 1 SATA(6TB)</b> interface, CH 1 & 2: 3MP @ 12 fps, CH 3 - 8:1920x1080P: 12 fps/ch, 260 1U case-- <b>HDMI output HD1080p-Metal</b>	IRR 30,700,000	
43	DVR-208Q-K1	Connectable to turbo HD, AHD, HDCVI and analog cameras. 2-ch 1080p IP cameras input. Long distance transmission over UTP and coaxial cable One key enable H.264+ compression. Up to 3 MP resolution for recording of the first 2 channels. Supports real-time 1080p lite. Simultaneous HDMI/VGA output at up to 1920 x 1080 resolution. One SATA interface (up to 6TB capacity per HDD).	IRR 27,070,000	
44	DVR-208U-F1	Recording Capability <b>5MP/3MP</b> <b>8-ch -HD-TVI/AHD/CVI/CVBS</b> video & 1-ch audio input- <b>4-ch IP video input(up to 6MP resolution), 1 SATA(6 TB)</b> interface,5MP@12fps,4MP@15fps,3MP@18fps,1080p/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N), 315 1U case-- <b>HDMI output 4K-Metal</b>	IRR 38,140,000	

45	DVR-208U-K1	8 Channel DVR,Support HD-TVI, AHD, HD-CVI and analog cameras Supports 4 x IP Camera,1080P resolution real-time recording 8MP recording @ 8fps,VGA output at up to 1920 x 1080P resolution HDMI output at up to 4K (3840 x 2160) resolution,Supports h.265+ Support up to 8-ch synchronous playback,Internet & Smart Phone compatible	IRR 41,080,000	
46	<b>Digital Video Recorder</b>			
47	DVR-116G-F1	16-ch 1080p Mini 1U Lite H.264 DVR, 5 signals input adaptively (HDTV/AHD/CVI/CVBS/IP),Long distance transmission over UTP and coaxial cable,H.265 Pro+ compression to improve encoding efficiency and reduce data storage costsSupports 1080p lite,Encoding ability up to 1080p lite @ 12 fps,One HDD for continuous video recording,Smart search for efficient playback.	IRR 21,000,000	
48	DVR-216G-F1	Recording Capability 3MP 16-ch HD-TVI/AHD/CVI/CVBS video & 1-ch audio input, -2-ch IP video input(up to HD1080p resolution), 1 SATA(6TB)- interface, CH 1 - 4: 3MP @ 12 fps, CH 5 - 16:1920x1080P: 12 fps/ch, 260 1U case-HDMI output 1ch 4k-Metal	IRR 26,570,000	
48	DVR-216G-K1	Recording Capability 3MP 16-ch HD-TVI/AHD/CVI/CVBS video & 1-ch audio input, -2-ch IP video input(up to HD1080p resolution), 1 SATA(6TB)- interface, CH 1 - 4: 3MP @ 12 fps, CH 5 - 16:1920x1080P: 12 fps/ch, 260 1U case-HDMI output 1ch 4k-Metal	IRR 26,570,000	
49	DVR-216Q-F1	Recording Capability 3MP 16-ch HD-TVI/AHD/CVI/CVBS video & 1-ch audio input, -2-ch IP video input(up to HD1080p resolution), 1 SATA(6TB)- interface, CH 1 - 4: 3MP @ 12 fps, CH 5 - 16:1920x1080P: 12 fps/ch, 260 1U case-HDMI output 1ch 4k-Metal	IRR 37,620,000	
50	DVR-216Q-K1	One-key enable H.265+ compression Self adaptive: TVI Turbo HD, AHD, HD-CVI & analog inputs Accepts 16 BNC analog video inputs Up to 8ch IP video input (6MP) Max 24ch: 16 HD and 8 IP Long distance transmission over UTP & coaxial cable Supports real-time 1080P lite	IRR 46,440,000	
51	DVR-216Q-K2	One-key enable H.265+ compression Self adaptive: TVI Turbo HD, AHD, HD-CVI & analog inputs Accepts 16 BNC analog video inputs Up to 8ch IP video input (6MP) Max 24ch: 16 HD and 8 IP Long distance transmission over UTP & coaxial cable Supports real-time 1080P lite	IRR 48,820,000	
52	DVR-216U-F2	Recording Capability 5MP/3MP 16-ch- HD-TVI/AHD/CVI/CVBS video & 1-ch audio input,- 8-ch IP video input(up to 6MP resolution), 2 SATA (6 TB)- interface,5MP@12fps,4MP@15fps,3MP@18fps,1080p/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N), 380 1U case-HDMI output 1ch 4K-Metal-	IRR 72,210,000	
53	DVR-216U-K2	DVR 16 Channels HD 8 Megapixel,Interfaces input: 16 video / 1 Audio, ( Support (TVI - AHD - CVI - CVBS,HDMI, VGA Outputs, 2 USB Support H.265+ compression, 2SATA up to 8TB capacity per HDD,Up to 8-ch,6MP IP cameras input, Up to 8 MP resolution for recording	IRR 81,300,000	