







































| Hilook-NVR | | | | |
|------------|--|-----------------------|---|--|
| Items | Description | User Price | | |
| 1 | IPC-B120 1/2.8" progressive scan CMOS-1920 × 1080@30fps - 2.8 mm fixed lens- H.264+, H.264- Color: 0.01 Lux @(F1.2, AGC ON), 0.028 Lux @(F2.0, AGC ON)-BLC/3D DNR-IP67- Digital WDR | IRR 14,280,000 |  | |
| 2 | IPC-B120H 2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.265+/H265/H.264+&H.264, 3D DNR, - 2.8/4/6mm fixed lens BLC, DC12V & PoE,- up to 30m IR -Support mobile monitoring via Hik-Connec *power supply no included- DWDR -Front Cover: Metal-Back Cover & Bracket: Plastic-IP67 | IRR 15,050,000 |  | |
| 3 | IPC-B121H 1/2.8" progressive scan CMOS 3D DNR 1920 × 1080@30fps Up to 30 m IR range 2.8 mm/4 mm fixed lens IP67, DWDR, H265 | IRR 15,050,000 |  | |
| 4 | IPC-B140H 4MP- 1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264, 3D DNR, BLC, DWDR- DC12V & PoE, 2.8/4/6mm fixed lens , Support mobile monitoring via Hik-up to 30m IR , Connec *power supply no included-Front Cover: Metal Back Cover & Bracket: Plastic-IP67 | IRR 18,610,000 |  | |
| 4 | IPC-B140H-M 4MP- 1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264, 3D DNR, BLC, DWDR- DC12V & PoE, 2.8/4/6mm fixed lens , Support mobile monitoring via Hik-up to 30m IR , Connec *power supply no included-Front Cover: Metal Back Cover & Bracket: Plastic-IP67 | IRR 20,360,000 |  | |
| 5 | IPC-B150H-M High quality imaging with 5 MP resolution Efficient H.265+ compression technology to save bandwidth and storage Clear imaging against strong back light due to 120 dB true WDR technology Water and dust resistant (IP67) 3D DNR technology delivers clean and sharp images Easy installation with Power over Ethernet (PoE) technology | IRR 22,620,000 |  | |
| 6 | IPC-B220 1/2.8" progressive scan CMOS - Up to 2.0 megapixel high resolution-H264- 4 mm Lens-Up to 30 m IR distance- Dual stream- DWDR -3D DNR (Digital Noise Reduction)-BLC-IP67- Mobile monitoring via mobile application | IRR 16,240,000 |  | |
| 7 | IPC-B220-D 1/2.8" progressive scan CMOS - Up to 2.0 megapixel high resolution-H264- 4 mm Lens-Up to 30 m IR distance- Dual stream- DWDR -3D DNR (Digital Noise Reduction)-BLC-IP67- Mobile monitoring via mobile application- D model only support 12VDC power supply | IRR 15,520,000 |  | |

| | | | | |
|----|--------------------------|--|----------------|---|
| 8 | IPC-T120 | 2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), DWDR - H.264+&H.264-, 2.8/4/6mm fixed lens- BLC, - DC12V & PoE, -up to 10m IR- Support mobile monitoring via Hik-Connect *power supply no included- Eyeball:Plastic-Cover: Plastic-Indoor-ip67 | IRR 14,900,000 |  |
| 9 | IPC-T120-D | 1/2.8" progressive scan CMOS-Up to 2.0 megapixel -2.8 mm fixed focal lens-H264+ - 10 m IR range-Dual stream-DWDR-3D DNR (Digital Noise Reduction)- Mobile monitoring via mobile application-IP 67- D model only support 12VDC power supply | IRR 14,170,000 |  |
| 10 | IPC-T220-H | 2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.265+/H265/H.264+&H.264, 3D DNRDWDR, BLC, DC12V & PoE,-up to 30m IR-Support mobile monitoring via HikConnec *power supply no included2.8/4/6mm fixed lens-Eyeball: MetalCover: Plastic-IP67 | IRR 17,190,000 |  |
| 11 | IPC-T220 | 1/2.8" progressive scan CMOS BLC/3D DNR,1920 x 1080@30fps,IP67 2.8, 4, 6 mm fixed lens,Digital WDR,H.264+, H.264 Color: 0.01 Lux @(F1.2, AGC ON), 0.028 Lux @(F2.0, AGC ON); | IRR 16,980,000 |  |
| 12 | IPC-T240H | 4MP-1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264, up to 30m IR- 3D DNR-DWDR, BLC, DC12V & PoE- 2.8/4/6mm fixed lens,--Support mobile monitoring via Hik-Connec *power supply no included-Eyeball: Metal-Cover: Plastic- IP67 | IRR 21,360,000 |  |
| 13 | IPC-D120 | 1/2.8" progressive scan CMOS-2 MP-1920 x 1080@30fps-2.8mm fixed lens-H.264+, H.264-Color: 0.01 Lux @(F1.2, AGC ON), 0.028 Lux @(F2.0, AGC ON)- BLC/3D DNR-IP67-Digital WDR- IK 10 | IRR 15,600,000 |  |
| 14 | IPC-D120H | 2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.265+/H265/H.264+&H.264, 3D DNR,--2.8/4/6mm fixed lens- BLC, DC12V & PoE,DWDR-Support mobile monitoring via Hik-Connect *power supply no included-up to 30m IR-Base: Metal-Cover: Plastic-IP67, IK10 | IRR 16,040,000 |  |
| 15 | IPC-D140H | 4.0 MP IR NetworkDome Camera,1/3" progressive scan CMOS, 3D DNR (Digital Noise Reduction), 2560 x 1440@20fps Up to 30 m IR range, 2.8 mm/4 mm/6 mm fixed lens,PoE (Power over Ethernet),H.265+, H.265, H.264+, H.264 IP67, IK10, Dual stream, 120 dB WDR. | IRR 19,780,000 |  |
| 16 | IPC-D150H | High quality imaging with 5 MP resolution Efficient H.265+ compression technology to save bandwidth and storage Clear imaging against strong back light due to 120 dB true WDR technology Water and dust resistant (IP67) and vandal resistant (IK10) 3D DNR technology delivers clean and sharp images Easy installation with Power over Ethernet (PoE) technology | IRR 19,940,000 |  |
| 17 | Vari-Focal Series | | | |
| 18 | IPC-B620H-V | 2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N),H.265+/H265/H.264+&H.264, 3D DNR ,DWDR- BLC, DC12V & PoE, TF card slot, up to 30m IR-Support mobile monitoring via Hik-Connect *power supply no included-2.8~12mm vari-focal lens-Body&Bracket: Metal-SunShield: Plastic-IP67 | IRR 33,050,000 |  |
| 19 | IPC-B620H-Z | 2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N),H.265+/H265/H.264+&H.264, 3D DNR, BLC, -up to 30m IR-DC12V & PoE, -DWDR- TF card slot,-Support mobile monitoring via Hik-Connect *power supply no included-2.8~12mm motorized vari-focal lens- Body&Bracket: Metal-SunShield: Plastic-IP67 | IRR 37,550,000 |  |
| 20 | IPC-B640H-V | 4MP- 1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264, 3D DNR, BLC, up to 30m IR- DC12V & PoE, TF card slot, WDR-Support mobile monitoring via Hik-Connect *power supply no included-2.8~12mm vari-focal lens-Body&Bracket: Metal-SunShield: Plastic-IP67 | IRR 36,560,000 |  |

| | | | | |
|----|---|--|-----------------|---|
| 21 | IPC-B640H-Z | 4MP- 1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264, 3D DNR, BLC, up to 30m IR- DC12V & PoE, TF card slot, -WDR- Support mobile monitoring via Hik-Connect *power supply no included-2.8~12mm motorized vari-focal lens-Body&Bracket: Metal-SunShield: Plastic-IP67 | IRR 39,160,000 |  |
| 22 | IPC-T620-Z | 2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.264+&H.264, 3D DNR, BLC, -WDR- up to 30m IR-DC12V & PoE, Support mobile monitoring via Hik-Connect *power supply no included 2.8~12mm VF lens- Eyeball: MetalCover: Plastic-IP67 | IRR 33,620,000 |  |
| 23 | IPC-D620H-V | 2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.265+/H265/H.264+&H.264, DWDR- 3D DNR, BLC, 2.8~12mm varifocal lens - DC12V & PoE, TF card slot, up to 30m IR-- Support mobile monitoring via Hik-Connect *power supply no included -Full Metal-IP67, IK10 | IRR 32,090,000 |  |
| 24 | IPC-D620H-Z | 1/2.8" progressive scan CMOS-2 MP-1920 x 1080@30fps- 2.8 mm to 12 mm manual/motorized (with -Z) vari-focal lens- H.265+, H.265, H.264+, H.264-Dual stream- DWDR -3D DNR (Digital Noise Reduction)-Up to 30 m IR range-PoE (Power over Ethernet)- IP67, IK10 | IRR 35,900,000 |  |
| 25 | IPC-D640H-V | 4MP-1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264, WDR, 3D DNR, BLC, up to 30m IR- DC12V & PoE, TF card slot--2.8~12mm vari-focal lens- Support mobile monitoring via Hik-Connect *power supply no included - Full Metal-IP67, IK10 | IRR 35,380,000 |  |
| 26 | IPC-D640H-Z | 4MP-1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264, WDR, 3D DNR, BLC, up to 30m IR- DC12V & PoE, TF card slot--2.8~12mm vari-focal lens- Support mobile monitoring via Hik-Connect *power supply no included - Full Metal-IP67, IK10 | IRR 38,060,000 |  |
| 27 | PanoVu Mini Series IR Network PTZ Camera | | | |
| 28 | PTZ-P332ZI-DE3 | System Functions 3-ch panoramic images in different directions and 1-ch close-up image PTZ linkage Up to 10 m IR radius Panoramic Camera Three 1/2.8" progressive scan CMOS 3-ch 1920 x 1080@30fps resolution Horizontal FOV: 128.5° x 3 PTZ Camera 1/2.8" progressive scan CMOS Up to 1920 x 1080@30fps resolution 4x optical zoom, 8x digital zoom | IRR 159,000,000 |  |
| 29 | IP PTZ Camera | | | |
| 30 | PTZ-N4215-DE3 | 1/2.8" progressive scan CMOS Up to 1920 x 1080 resolution Min. illumination Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR 15x optical zoom, 16x digital zoom 120dB WDR, 3D DNR, HLC, BLC 12 VDC & PoE+ (802.3at, class4) Support H.265+/H.265 video compression Up to 24 programmable privacy masks Support ROI | IRR 72,810,000 |  |
| 31 | PTZ-N4215I-DE | 1/2.8" progressive scan CMOS Up to 1920 x 1080 resolution Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR Up to 100 m IR distance 15x optical zoom, 16x digital zoom 120dB WDR, 3D DNR, HLC, BLC, Smart IR 12 VDC & PoE+ (802.3at, class4) Support H.265+/H.265 video compression Up to 24 programmable privacy masks Support ROI | IRR 77,880,000 |  |

| | | | | |
|----|-------------------------------|--|----------------|---|
| 32 | PTZ-N4225I-DE | 1/2.8" progressive scan CMOS Up to 1920 × 1080 resolution Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR Up to 100 m IR distance 25× optical zoom, 16× digital zoom 120dB WDR, 3D DNR, HLC, BLC, Smart IR 12 VDC & PoE+ (802.3at, class4) Support H.265+/H.265 video compression Up to 24 programmable privacy masks Support ROI | IRR 94,590,000 |  |
| 33 | PTZ-N2404I-DE3 | Two-inch 4 MP camera with pan, tilt and zoom (4x) ability Efficient H.265+ compression technology to save bandwidth and storage Clear imaging against strong back light due to 120 dB true WDR technology Great night-time performance with up to 20 m enhanced IR Water and dust resistant (IP66), and vandal proof (IK10) | IRR 50,020,000 |  |
| 34 | Network Video Recorder | | | |
| 35 | NVR-104-B | Full channel recording at up to 4 MP resolution-40Mbps Bit Rate Input Max (up to 4-ch IP video), Output Bandwidth 40Mbps- H.264, 1 SATA interface 6TB, mini 1U case(Plastic)-HDMI Output 1, up to 1080P-Decoding Capability- 2-ch@ 4MP-4-ch@1080p | IRR 9,810,000 |  |
| 36 | NVR-108-B | Full channel recording at up to 4 MP resolution-60Mbps Bit Rate Input -Max (up to 8-ch IP video), Output Bandwidth 40Mbps- H.264, 1 SATA interface 6TB, mini 1U case(Plastic)-HDMI Output 1, up to 1080P-Decoding Capability-2-ch@4 MP, 4-ch@1080p | IRR 12,030,000 |  |
| 37 | NVR-108-B/8p | 4-ch Mini 1U 4 PoE 4K NVR, Up to 8 channel IP cameras can be connected Plug & Play with 8 Power-over-Ethernet (PoE) interfaces Supports decoding H.264+/H.264 multiple video formats Up to 4-ch @ 1080p decoding capacity 1 HDD for continuous video recording | IRR 30,490,000 |  |
| 38 | NVR-104MH-C | Recording at up to 8 MP resolution 40Mbps Bit Rate -Input Max (up to 4-ch IP video UP to 8MP), Output Bandwidth 80Mbps- H.265-, 1 SATA (6TB) interface, standalone 1U 315 case(Metal)-HDMI Output 1CH 4K, --Decoding Capability 1-ch @ 8 MP / 4-ch @ 1080p | IRR 15,590,000 |  |
| 39 | NVR-104MH-D | Up to 4 channel IP cameras can be connected Supports decoding H.265+/H.265/H.264+/H.264 multiple video formats Up to 4-ch @ 1080p decoding capacity 1 HDD for continuous video recording. | IRR 12,510,000 |  |
| 40 | NVR-104MH-D/4P | Up to 4 channel IP cameras can be connected Plug & Play with 4 Power-over-Ethernet (PoE) interfaces Supports decoding H.265+/H.265/H.264+/H.264 multiple video formats Up to 4-ch @ 1080p decoding capacity 1 HDD for continuous video recording | IRR 21,660,000 |  |
| 41 | NVR-104MH-C/4P | Recording at up to 8 MP resolution-40Mbps Bit Rate Input- Max (up to 4-ch IP video UP to 8 MP), Output Bandwidth 80Mbps- H.265-, 1SATA(6TB) interface, 4 independent PoE network interfaces, 1U 315 case(Metal)-HDMI Output 1ch 4K- Decoding Capability 1-ch @ 8 MP 4-ch @ 1080P | IRR 22,860,000 |  |
| 42 | NVR-108MH-C | Recording at up to 8 MP resolution-80Mbps Bit Rate Input- Max (up to 8-ch IP video UP to 8 MP), Output Bandwidth 80Mbps- H.265, 1 SATA interface(6TB), standalone 1U 315 case(Metal)-HDMI Output 1CH 4K, Decoding Capability: -1-ch @ 8 MP / 4-ch @ 1080p | IRR 20,970,000 |  |
| 43 | NVR-108MH-D | IP video input 8ch, Incoming bandwidth 60 Mbps Outgoing, bandwidth 60 Mbps, Recording resolution 4 MP/3 MP/1080p/UXGA /720p/VGA/4CIF/DCIF/ 2CIF/CIF/QCIF, H.265+/H.265/ H.264+/H.264, 1 SATA interface, Capacity Up to 6TB capacity for each disk, | IRR 16,800,000 |  |

| | | | | |
|----|------------------------|---|-----------------------|--|
| 44 | NVR-208MH-C | Recording at up to 8 MP resolution-80Mbps Bit Rate Input- Max (up to 8-ch IP video UP to 8 MP),Output Bandwidth 80Mbps- H.265, 2 SATA interface(6TB), standalone 1U 315 case(Metal)-HDMI Output 1CH 4K,Decoding Capability: -1-ch @ 8 MP / 4-ch @ 1080p | IRR 22,820,000 |  |
| 45 | NVR-108MH-C/8P | Recording at up to 8 MP resolution-80Mbps Bit Rate Input- Max (up to 8-ch IP video UP to 8MP),Output Bandwidth 80Mbps-, H.265, 1 SATA interface(6 TB),8 independent PoE network interfaces, standalone 1U 315 case(Metal)-HDMI Output 1ch 4k, - Decoding Capability:1-ch @ 8 MP / 4-ch @ 1080p | IRR 53,500,000 |  |
| 46 | NVR-108M-D/8P | IP video input 8ch, Incoming bandwidth 60 Mbps Outgoing,bandwidth 60 Mbps, Recording resolution 4 MP/3 MP/1080p/UXGA /720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF, H.265+/H.265/ H.264+/H.264, 1 SATA interface,Capacity Up to 6TB capacity for each disk, | IRR 47,520,000 |  |
| 47 | NVR-116MH-C | Recording at up to 8 MP resolution-160Mbps Bit Rate Input- Max (up to 16-ch IP video UP to 8MP),Output Bandwidth 80Mbps-, H.265, 1 SATA interface(6TB), standalone 1U 315 case(Metal)-HDMI Output 1CH 4K, Decoding Capability: 1-ch @ 8 MP / 4-ch @ 1080p | IRR 24,530,000 |  |
| 48 | NVR-216MH-C | Recording at up to 8 MP resolution-160Mbps Bit Rate Input Max (up to 16-ch IP video),Output Bandwidth 80Mbps, - H.265-2,SATA up to 6TB per HDD interface, standalone 1U 385 case(Metal)-HDMI Output1 ch 4k -Decoding Capability: 1-ch @ 8 MP / 4-ch @ 1080p | IRR 29,190,000 |  |
| 49 | NVR-216MH-C/16P | Recording at up to 8 MP resolution-160Mbps Bit Rate Input Max (up to 16-ch IP video)Output Bandwidth 80Mbps, H.265, 2 SATA(up to 6TB per HDD) interface,16 independent PoE network interfaces, standalone 1U 385 case(Metal)-HDMI Output1 ch 4k, -Decoding Capability 1-ch @ 8 MP / 4-ch @ 1080p | IRR 62,680,000 |  |