

لیست قیمت فروردين 1400

Tiandy

TC-C32GN-Lite Spec: I5/E/4mm

2MP IR Bullet Camera
1/2.9" 2MP progressive scan CMOS
Min. illumination Color: 0.02Lux@F2.0
4mm Fixed Lens, FOV 82 D
1920x1080@30 fps
S+265/H.265/H.264 dual-stream encoding
WDR(80dB), Day/Night, BLC, 3D DNR, HLC
Smart Defog
Smart IR, IR Range: 50m
Metal+Makrolon, PoE, IP67



12.200.000

TC-C32HN-Lite Spec: I3/E/2.8mm

2MP IR Turret Camera
1/2.9" 2MP progressive scan CMOS
Min. illumination Color: 0.02Lux@F2.0
2.8mm Fixed Lens, FOV 97.5 D
1920x1080@30 fps
S+265/H.265/H.264 dual-stream encoding
WDR(80dB), Day/Night, BLC, 3D DNR, HLC
Smart Defog
Smart IR, IR Range: 30m
Metal+Makrolon, PoE, IP66



12.200.000

TC-C32JN-Lite Spec: I5/E/4mm

2MP IR Bullet Camera
1/2.9" 2MP progressive scan CMOS
Min. illumination Color: 0.02Lux@F2.0
4mm Fixed Lens, FOV 82 D
1920x1080@30fps
S+265/H.265/H.264 dual-stream encoding
WDR(80dB), Day/Night, BLC, 3D DNR, HLC
Smart Defog
Smart IR, IR Range: 50m
Metal, PoE, IP67



16.000.000

Super Starlight TC-C32GP-Lite Spec : I5/E/C/4mm

2MP Super Starlight IR Bullet Camera
1/2.8" 2MP progressive scan Sony CMOS
Min. illumination Color: 0.0008Lux@F1.6
4mm Fixed Lens, FOV 87.5 D
1920x1080@30fps
S+265/H.265/H.264 dual-stream encoding
WDR (80dB), Day/Night, BLC, 3D DNR, HLC
Smart Defog
Metal+Plastic Housing
Smart IR, IR Range: 30m
Metal+Makrolon, PoE, IP67



19.200.000



TC-C32WN-Lite Spec: I5/E/Y/2.8mm

2MP IR Bullet Camera
1/2.9" 2MP progressive scan CMOS
Min. illumination Color: 0.02Lux@F2.0
2.8mm Fixed Lens, FOV 97.5 D
1920x1080@30fps
S+265/H.265/H.264 dual-stream encoding
WDR(80dB), Day/Night, BLC, 3D DNR, HLC
VCA (Tripwire/Perimeter)
Smart Defog
Mic-in
Micro SD card 512GB
Reset Button
Smart IR, IR Range: 50m
Metal+Makrolon, PoE, IP67



Call

TC-C32XN-Lite Spec: I3/E/Y/2.8mm

2MP IR Bullet Camera
1/2.9" 2MP progressive scan CMOS
Min. illumination Color: 0.02Lux@F2.0
2.8mm Fixed Lens, FOV 97.5 D
1920x1080@30fps
S+265/H.265/H.264 dual-stream encoding
WDR(80dB), Day/Night, BLC, 3D DNR, HLC
VCA (Tripwire/Perimeter)
Smart Defog
Built-in Mic
Micro SD card 512GB
Reset Button
Smart IR, IR Range: 30m
Metal+Makrolon, PoE, IP67



Call

Super Starlight TC-C32WP-Lite Spec: I5/E/Y/M/2.8mm

2MP Super Starlight IR Bullet Camera
1/2.8" 2MP progressive scan **Sony** CMOS
Min. illumination Color: 0.0008Lux@F1.6
2.8mm Fixed Lens, FOV 107 D
1920x1080@30fps
S+265/H.265/H.264 dual-stream encoding
WDR(80dB), Day/Night, BLC, 3D DNR, HLC
VCA (Tripwire/Perimeter)
Smart Defog
Built-in Mic
Micro SD card 512GB
Reset Button
Smart IR, IR Range: 50m
Full Metal, PoE, IP67



Call

Super Starlight TC-C32WP-Lite Spec: I5/E/Y/M/4mm

2MP Super Starlight IR Bullet Camera
1/2.8" 2MP progressive scan **Sony** CMOS
Min. illumination Color: 0.0008Lux@F1.6
4mm Fixed Lens, FOV 87.5 D
1920x1080@30fps
S+265/H.265/H.264 dual-stream encoding
WDR(80dB), Day/Night, BLC, 3D DNR, HLC
VCA (Tripwire/Perimeter)
Smart Defog
Built-in Mic
Micro SD card 512GB
Reset Button
Smart IR, IR Range: 50m
Full Metal, PoE, IP67



Call

TC-C32KN-Lite Spec: I3/E/Y/2.8mm

2MP IR Bullet Camera
1/2.9" 2MP progressive scan CMOS
Min. illumination Color: 0.02Lux@F2.0
2.8mm Fixed Lens, FOV 97.5 D
1920x1080@30fps
S+265/H.265/H.264 dual-stream encoding
WDR(80dB), Day/Night, BLC, 3D DNR, HLC
VCA (Tripwire/Perimeter)
Smart Defog
Built-in Mic
Micro SD card 512GB
Reset Button
Smart IR, IR Range: 30m
Metal-Makrolon, PoE, IP67, IK10



Call

Color Maker TC-C32FP-Lite Spec: W/E/Y/2.8mm

2MP Color Maker Turret Camera
1/2.9" 2MP progressive scan **Sony** CMOS
Min. illumination Color: 0.0008Lux@F1.6
2.8mm fixed lens, FOV 100.5 D
1920x1080@30fps
S+265/H.265/H.264 dual-stream encoding
WDR(80dB), Day/Night, BLC, 3D DNR, HLC
VCA (Tripwire/Perimeter)
Smart Defog
Built-in Mic
Warm Light, Range: 15m
Metal-Makrolon, PoE, IP66



Call



Starlight TC-C32WS-Pro Spec: I5/E/Y/M/4mm

2MP Starlight IR Bullet Camera (**Turbo AI**)
1/2.8" 2MP progressive scan **Sony** CMOS
Min. illumination Color: 0.001Lux@F1.6
4mm Fixed Lens, FOV 87.5 D
1920x1080@30fps
S+265/H.265/H.264 dual-stream encoding
WDR(120dB), Day/Night, BLC, 3D DNR, HLC
VCA (Tripwire/Double Tripwire/Perimeter/Object
Abandon/Object Lost/Running/Loitering/
Parking/Crowded/Video Abnormal/Heat
Map/People Counting)
Support Human/Vehicle Classification
Support Face Capture Mode
Smart Defog
Built-in Mic
Micro SD card 512GB
Reset Button
Smart IR, IR Range: 50m
Full Metal, PoE, IP67



Call

Starlight TC-C32KS-Pro Spec: I3/E/Y/M/2.8mm

2MP Starlight IR Dome Camera (**Turbo AI**)
1/2.8" 2MP progressive scan **Sony** CMOS
Min. illumination Color: 0.001Lux@F1.6
2.8mm Fixed Lens, FOV 107 D
1920x1080@30fps
S+265/H.265/H.264 dual-stream encoding
WDR(120dB), Day/Night, BLC, 3D DNR, HLC
VCA (Tripwire/Double Tripwire/Perimeter/Object
Abandon/Object Lost/Running/Loitering/
Parking/Crowded/Video Abnormal/Heat Map/
People Counting)
Support Human/Vehicle Classification
Support Face Capture Mode
Smart Defog
Built-in Mic
Micro SD card 512GB
Reset Button
Smart IR, IR Range 30m
Full Metal, PoE, IP67, IK10



Call

TC-C33WN-Lite Spec: I5/E/Y/2.8mm

3MP IR Bullet Camera
1/2.7" 3MP progressive scan CMOS
Min. illumination Color: 0.02Lux@F2.0
2.8mm Fixed Lens, FOV 100 D
2304x1296@20fps
S+265/H.265/H.264 dual-stream encoding
WDR(80dB), Day/Night, BLC, 3D DNR, HLC
VCA (Tripwire/Perimeter)
Smart Defog
Built-in Mic
Micro SD card 512GB
Reset Button
Smart IR, IR Range: 50m
Metal+Makrolon, PoE, IP67



16.100.000

TC-C33XN-Lite Spec: I5/E/Y/2.8mm

3MP IR Bullet Camera
1/2.7" 3MP progressive scan CMOS
Min. illumination Color: 0.02Lux@F2.0
2.8mm Fixed Lens, FOV 100 D
2304x1296@20fps
S+265/H.265/H.264 dual-stream encoding
WDR(80dB), Day/Night, BLC, 3D DNR, HLC
VCA (Tripwire/Perimeter)
Smart Defog
Built-in Mic
Micro SD card 512GB
Reset Button
Smart IR, IR Range: 30m
Metal+Makrolon, PoE, IP67



16.100.000

TC-C34GN-Lite Spec: I5/E/C/4mm

4MP IR Bullet Camera
1/2.9" 4Megapixel progressive CMOS
Min. illumination Color: 0.02Lux@F2.0
4mm Fixed Lens, FOV 87.5 D
2560x1440@25fps
S+265/H.265/H.264 dual-stream encoding
WDR(80dB), Day/Night, BLC, 3D DNR, HLC
Smart Defog
Smart IR, IR Range: 50m
Metal+Makrolon, PoE, IP67



18.150.000

TC-C34HN-Lite Spec: I3/E/C/2.8mm

4MP IR Bullet Camera
1/2.9" 4Megapixel progressive CMOS
Min. illumination Color: 0.02Lux@F2.0
2.8mm Fixed Lens, FOV 105.5 D
2560x1440@25fps
S+265/H.265/H.264 dual-stream encoding
WDR(80dB), Day/Night, BLC, 3D DNR, HLC
Smart Defog
Built-in Mic
Smart IR, IR Range: 30m
Metal+Makrolon, PoE, IP66



18.150.000



TC-C34JN-Lite Spec: I5/E/C/4mm

4MP IR Bullet Camera
1/2.7" 4Megapixel progressive CMOS
Min. illumination Color: 0.02Lux@F2.0
4mm Fixed Lens, FOV 87.5 D
2560x1440@25fps
S+265/H.265/H.264 dual-stream encoding
WDR(80dB), Day/Night, BLC, 3D DNR, HLC
Smart Defog
Smart IR, IR Range: 50m
Full Metal, PoE, IP67



20.500.000

Starlight TC-C34JS-Lite Spec: I5/E/C/4mm

4MP Starlight IR Bullet Camera
1/2.7" 4Megapixel progressive CMOS
Min. illumination Color: 0.005Lux@F1.6
4mm Fixed Lens, FOV 91 D
2560x1440@25fps
S+265/H.265/H.264 dual-stream encoding
WDR(80dB), Day/Night, BLC, 3D DNR, HLC
Smart Defog
Smart IR, IR Range: 50m
Full Metal, PoE, IP67



23.500.000

Starlight TC-C34GS-Lite Spec: I5/E/C/4mm

4MP Starlight IR Bullet Camera
1/2.7" 4Megapixel progressive CMOS
Min. illumination Color: 0.005Lux@F1.6
4mm Fixed Lens, FOV 91 D
2560x1440@25fps
S+265/H.265/H.264 dual-stream encoding
WDR(80dB), Day/Night, BLC, 3D DNR, HLC
Smart Defog
Smart IR, IR Range: 50m
Metal+Makrolon, PoE, IP67



20.000.000

Starlight TC-C34WS-Lite Spec: I5/E/Y/M/2.8mm

4MP Starlight IR Bullet Camera
1/2.8" 4MP progressive scan Sony CMOS
Min. illumination Color: 0.002Lux@F1.6
2.8mm Fixed Lens, FOV 94 D
2592x1520@25 fps
S+265/H.265/H.264 dual-stream encoding
WDR(120dB), Day/Night, BLC, 3D DNR, HLC
VCA (Tripwire/Perimeter)
Smart Defog
Built-in Mic
Micro SD card 512GB
Reset Button
Smart IR, IR Range: 50m
Full Metal, PoE, IP67



Call

Starlight TC-C34KS-Lite Spec: I3/E/Y/2.8mm

4MP Starlight IR Bullet Camera
1/2.8" 4MP progressive scan Sony CMOS
Min. illumination Color: 0.002Lux@F1.6
2.8mm Fixed Lens, FOV 94 D
2592x1520@25 fps
S+265/H.265/H.264 dual-stream encoding
WDR(120dB), Day/Night, BLC, 3D DNR, HLC
VCA (Tripwire/Perimeter)
Smart Defog
Built-in Mic
Micro SD card 512GB
Reset Button
Smart IR, IR Range: 30m
Metal+Makrolon, PoE, IP67, IK10



Call

Color Maker TC-C34UP-Lite Spec: W/E/Y/M/4mm

4MP Color Maker Bullet Camera
1/1.8" 4MP progressive scan CMOS
Min. illumination Color: 0.0002Lux@F1.0
4mm fixed lens, FOV 91 D
2560x1440@25 fps
S+265/H.265/H.264 dual-stream encoding
WDR(120dB), Day/Night, BLC, 3D DNR, HLC
VCA (Tripwire/Perimeter/
Smart Defog
Built-in Mic
Micro SD card 512GB
Reset Button
Warm Light, Range: 30m
Full Metal, PoE, IP67



Call



Starlight **TC-C35JS-Pro Spec: I5/E/M/4mm**

5MP Starlight IR Bullet Camera (**Turbo AI**)
1/2.8" 5MP progressive scan **Sony** CMOS
Min. illumination Color: 0.002Lux@F1.6
4mm Fixed Lens, FOV 80 D
2592x1944@20fps
S+265/H.265/H.264 dual-stream encoding
WDR(120dB), Day/Night, BLC, 3D DNR, HLC
VCA (Tripwire/Double Tripwire/Perimeter/Object
Abandon/Object Lost/Running/Loitering/
Parking/Crowed/Video Abnormal/Heat Map)
Smart Defog
Micro SD card 256GB
Reset Button
Smart IR, IR Range: 50m
Full Metal, PoE, IP67



Call

Starlight **TC-C35TS-Pro Spec: I8/A/E/Y/M/H/2.7~13.5mm**

5MP Starlight Motorized IR Bullet Camera (**Turbo AI**)
1/2.8" 5MP progressive scan **Sony** CMOS
Min. illumination Color: 0.001Lux@F1.6
2.7~13.5mm Motorized Lens, FOV 103.5~24 D
2592x1944@30fps / 1920x1080@60fps
S+265/H.265/H.264 dual-stream encoding
WDR(120dB), Day/Night, BLC, 3D DNR, HLC
VCA (Tripwire/Double Tripwire/Perimeter/Object
Abandon/Object Lost/Running/Loitering/
Parking/Crowed/Video Abnormal/Heat Map/People
Counting)
Support Human/Vehicle Classification
Support Face Capture Mode
Smart Defog
Audio I/O 1/1, Alarm I/O 2/1
Micro SD card 512GB
Reset Button
Smart IR, IR Range: 80m
Full Metal, PoE, IP67



Call

Starlight **TC-C35MS-Lite Spec: I3/A/E/Y/M/2.8-12mm**

5MP Starlight Motorized IR Dome Camera
1/2.8" 5MP progressive scan **Sony** CMOS
Min. illumination Color: 0.002Lux@F1.6
2.8~12mm Motorized Lens, FOV 100.5~27 D
2592x1944@20fps / 1920x1080@60fps
S+265/H.265/H.264 dual-stream encoding
WDR(120dB), Day/Night, BLC, 3D DNR, HLC
VCA (Tripwire/Perimeter)
Smart Defog
Built-in Mic
Micro SD card 512GB
Reset Button
Smart IR, IR Range: 30m
Full Metal, PoE, IP67, IK10



39.000.000

Starlight **TC-C35MS-Pro Spec: I5/A/E/Y/M/H/2.7-13.5mm**

5MP Starlight Motorized IR Dome Camera (**Turbo AI**)
1/2.8" 5MP progressive scan **Sony** CMOS
Min. illumination Color: 0.001Lux@F1.6
2.8~12mm Motorized Lens, FOV 103.5~24 D
2592x1944@30fps / 1920x1080@60fps
S+265/H.265/H.264 dual-stream encoding
WDR(120dB), Day/Night, BLC, 3D DNR, HLC
VCA (Tripwire/Double Tripwire/Perimeter/
Object Abandon/Object Lost/Running/
Loitering/Parking/Crowed/Video Abnormal/
Heat Map/People Counting)
Support Human/Vehicle Classification
Support Face Capture Mode
Smart Defog
Built-in Mic, Audio I/O 1/1, Alarm I/O 2/1
Micro SD card 512GB
Reset Button
Smart IR, IR Range: 50m
Full Metal, PoE, IP67, IK10



Call

Starlight **TC-C35US-Lite Spec: I8/A/E/Y/M/2.8~12mm**

5MP Starlight Motorized IR Bullet Camera
1/2.8" 5MP progressive scan **Sony** CMOS
Min. illumination Color: 0.002Lux@F1.6
2.8~12mm Motorized Lens, FOV 100.5~27 D
2592x1944@20fps
S+265/H.265/H.264 dual-stream encoding
WDR(120dB), Day/Night, BLC, 3D DNR, HLC
VCA (Tripwire/Perimeter)
Smart Defog
Built-in Mic
Micro SD card 512GB
Reset Button
Smart IR, IR Range: 80m
Full Metal, PoE, IP67



34.500.000

Starlight **TC-C35KS-Pro Spec: I3/E/Y/M/H/2.8mm**

5MP Starlight IR Dome Camera (**Turbo AI**)
1/2.8" 5MP progressive scan **Sony** CMOS
Min. illumination Color: 0.002Lux@F1.6
2.8mm Fixed Lens, FOV 98 D
2592x1944@30fps / 1920x1080@60fps
S+265/H.265/H.264 dual-stream encoding
WDR(120dB), Day/Night, BLC, 3D DNR, HLC
VCA (Tripwire/Double Tripwire/Perimeter/
Object Abandon/Object Lost/Running/
Loitering/Parking/Crowed/Video Abnormal/
Heat Map/People Counting)
Support Human/Vehicle Classification
Support Face Capture Mode
Smart Defog
Built-in Mic, Audio I/O 1/1, Alarm I/O 2/1
Micro SD card 512GB
Reset Button
Smart IR, IR Range: 30m
Full Metal, PoE, IP67, IK10



Call



Starlight TC-C35KS-Lite Spec: I3/E/Y/2.8mm

5MP Starlight IR Dome Camera
1/2.8" 5MP progressive scan Sony CMOS
Min. illumination Color: 0.002Lux@F1.6
2.8mm Fixed Lens, FOV 98 D
2592x1944@20fps
S+265/H.265/H.264 dual-stream encoding
WDR(120dB), Day/Night, BLC, 3D DNR, HLC
VCA (Tripwire/Perimeter)
Smart Defog
Built-in Mic
Micro SD card 512GB
Reset Button
Smart IR, IR Range: 30m
Metal+Makrolon, PoE, IP67, IK10



Call

Starlight TC-C38JS-Pro Spec: I5/E/M/4mm

8MP Starlight IR Bullet Camera (Turbo AI)
1/2.8" 8MP progressive scan Sony CMOS
Min. illumination Color: 0.01Lux@F2.0
4mm Fixed Lens, FOV 85 D
3840x2160@20fps
S+265/H.265/H.264 dual-stream encoding
WDR(120dB), Day/Night, BLC, 3D DNR, HLC
VCA (Tripwire/Double Tripwire/Perimeter/
Object Abandon/Object Lost/Running/
Loitering/Parking/Crowed/Video Abnormal/
Heat Map)
Smart Defog
Micro SD card 128GB
Reset Button
Smart IR, IR Range: 50m
Full Metal, PoE, IP67



Call

Starlight TC-C38TS-Pro Spec: I8/A/E/Y/M/H/2.7~13.5mm

8MP Starlight Motorized IR Bullet Camera (Turbo AI)
1/2.8" 8MP progressive scan Sony CMOS
Min. illumination Color: 0.01Lux@F1.6
2.7~13.5mm Motorized Lens, FOV 103~29 D
3840x2160@20fps
S+265/H.265/H.264 dual-stream encoding
WDR(120dB), Day/Night, BLC, 3D DNR, HLC
VCA (Tripwire/Double Tripwire/Perimeter/Object
Abandon/Object Lost/Running/Loitering/
Parking/Crowed/Video Abnormal/Heat Map/People
Counting)
Support Human/Vehicle Classification
Support Face Capture Mode
Smart Defog
Audio I/O 1/1, Alarm I/O 2/1
Micro SD card 512GB
Reset Button
Smart IR, IR Range: 80m
Full Metal, PoE, IP67



Call

Starlight TC-C38WS-Lite Spec: I5/E/Y/M/2.8mm

8MP Starlight IR Bullet Camera
1/2.8" 8MP progressive scan Sony CMOS
Min. illumination Color: 0.01Lux@F1.6
2.8mm Fixed Lens, FOV 96 D
3840x2160@20fps
S+265/H.265/H.264 dual-stream encoding
WDR(120dB), Day/Night, BLC, 3D DNR, HLC
VCA (Tripwire/Perimeter)
Smart Defog
Built-in Mic
Micro SD card 512GB
Reset Button
Smart IR, IR Range: 50m
Full Metal, PoE, IP67



Call

Starlight TC-C38KS-Lite Spec: I3/E/Y/2.8mm

8MP Starlight IR Dome Camera
1/2.8" 8MP progressive scan Sony CMOS
Min. illumination Color: 0.01Lux@F1.6
2.8mm Fixed Lens, FOV 96 D
3840x2160@20fps
S+265/H.265/H.264 dual-stream encoding
WDR(120dB), Day/Night, BLC, 3D DNR, HLC
VCA (Tripwire/Perimeter)
Smart Defog
Built-in Mic
Micro SD card 512GB
Reset Button
Smart IR, IR Range: 30m
Metal+Makrolon, PoE, IP67, IK10



Call

Starlight TC-C38KS-Pro Spec : I3/E/Y/M/H/2.8mm

8MP Starlight IR Dome Camera (Turbo AI)
1/2.8" 8MP progressive scan Sony CMOS
Min. illumination Color: 0.01Lux@F1.6
2.8mm Fixed Lens, FOV 96 D
3840x2160@20fps
S+265/H.265/H.264 dual-stream encoding
WDR(120dB), Day/Night, BLC, 3D DNR, HLC
VCA (Tripwire/Double Tripwire/Perimeter/
Object Abandon/Object Lost/Running/
Loitering/Parking/Crowed/Video Abnormal/
Heat Map/People Counting)
Support Human/Vehicle Classification
Support Face Capture Mode
Smart Defog
Built-in Mic, Audio I/O 1/1, Alarm I/O 2/1
Micro SD card 512GB
Reset Button
Smart IR, IR Range: 30m
Full Metal, PoE, IP67, IK10



Call



Starlight

TC-NCL514S

5MP Starlight IR Bullet Camera (4mm)
1/2.8" 5Megapixel progressive Sony CMOS
4mm fixed lens, FOV 81 D
2560x1920@20fps
S+265/H.265/H.264 dual-stream encoding
Min. illumination Color: 0.002Lux
WDR(80dB), 3DNR, Day/Night (ICR), HLC, BLC, Corridor Format
Smart Defog, ROI
VCA (Tripwire/Double Tripwire/Perimeter/Object Abandon/Object Lost/Running/Loitering/Parking/Crowd/Video Abnormal Detection/ Face Detection/ Demographics)
Max IR LEDs Length 50m, Smart IR
Metal+Makrolon, IP67, PoE



27.500.000

Starlight

TC-NCL522S

5MP Starlight IR Turret Camera
1/2.8" 5Megapixel progressive Sony CMOS
2.8mm Fixed lens, FOV 98 D
2560x1920@20fps
S+265/H.265/H.264 dual-stream encoding
Min. illumination Color: 0.002Lux
WDR(80dB), Day/Night (ICR), 3D DNR, BLC, HLC
VCA (Tripwire/Double Tripwire/Perimeter/Object Abandon/Object Lost/Running/Loitering/Parking/Crowd /Video Abnormal Detection/ Face Detection/ Demographics)
Smart Defog, ROI
Metal+Plastic Housing
Max IR LEDs Length 30m, Smart IR
Metal+Makrolon, IP66, PoE



27.500.000

TC-NC43M

4MP H.265 Motorized IR Bullet Camera
1/3" 4Megapixel progressive CMOS
Motorized Lens 2.8-12mm, FOV 92~30 D
Up to 2560x1440@25fps
Min. illumination Color: 0.02Lux
S+265/H.265/H.264/M-JPEG triple-stream encoding
WDR(120dB), BLC, 3D DNR, HLC, Corridor Format
Smart Defog, ROI
VCA (Tripwire/Double Tripwire/Perimeter/Object Abandon/Object Lost/Running/Loitering/Parking/Crowd/Audio Abnormal/Video Abnormal)
1/1 Audio in/Out, 2/1 Audio in/Out
RS485, USB, Micro SD card 128GB
Smart IR, IR Range: 50m
Full Metal, IP67, PoE



Call

TC-NC44M

4MP H.265 Motorized IR Dome Camera
1/3" 4Megapixel progressive CMOS
Motorized Lens 2.8-12mm, FOV 99~30 D
Up to 2560x1440@25fps
Min. illumination Color: 0.02Lux
S+265/H.265/H.264/M-JPEG Triple-stream encoding
WDR(120dB), Day/Night (ICR), BLC, 3D DNR, HLC, Corridor Format
Smart Defog, ROI
VCA (Tripwire/Double Tripwire/Perimeter/Object Abandon/Object Lost/Running/Loitering/Parking/Crowd/Audio Abnormal/Video Abnormal)
Smart Defog, ROI
Built in Mic
1/1CH Audio In/Out, 2/1 Alarm In/Out
Micro SD card 128GB
Smart IR, IR Range: 30m
Full Metal, IP66, IK10, PoE



Call



Starlight **TC-A3563-Ultra Spec:44X/I/A**

5MP 44x Super Starlight IR Face Capture AEW PTZ Camera
1/1.8" 5Megapixel Sony CMOS
Up to 3072x1728@20fps
Min. illumination Color: 0.0008Lux
S+265/H.265/H.264/MJPEG Triple-streams encoding
6mm~264mm 44x optical zoom
WDR(140dB), Dual IR Cut Filter, 3D-DNR, HLC, BLC
Smart Defog, ROI
Auto-Tracking Early Warning (AEW)
Support Human/Vehicle Classification
VCA (Tripwire/Double Tripwire/Perimeter/Object Abandon/
Object Lost/Running/Loitering/Parking/Face Detection/
People Counting/Crowded/Audio Abnormal/Video Abnormal/
On Duty Detection/Heatmap/Safety Helmet Detection)
500 presets,16 Cruise (32 preset per cruise),8 pattern
8/2 Alarm in/out, 1/1 Audio in/out
Micro SD card 128GB
Built-in Speaker, Wiper, RS-485
IR Distance up to 180m
IP66



Call

Starlight **TC-H326S-Pro Spec:33X/I/E/A**

2MP 33x Starlight IR POE PTZ Camera
1/2.8" 2Megapixel Sony CMOS
Min. illumination Color: 0.002Lux@F1.5
S+265/H.265/H.264/MJPEG Triple-streams encoding
Up to 1920X1080@60fps
4.6mm~152mm 33x optical zoom
WDR(140dB), Dual IR Cut Filter, 3D-DNR, HLC, BLC
Smart Defog, ROI
Support Auto Tracking
VCA (Tripwire/Double Tripwire/Perimeter/Object
Abandon/Object Lost/Running/Loitering/Parking/
Audio Abnormal/Video Abnormal/Heatmap)
Up to 500 presets,16 Cruise,8 pattern
1/1 Alarm in/out, 1/1 Audio in/out
Micro SD card 128GB
Smart IR, IR Range: 150m
IP66, PoE+



Call

Starlight **TC-H326S-Pro Spec:33X/I/E++/A**

2MP 33x Starlight IR POE PTZ Camera
1/2.8" 2Megapixel Sony CMOS
Min. illumination Color: 0.001Lux@F1.5
S+265/H.265/H.264/MJPEG Triple-streams encoding
Up to 1920X1080@60fps
4.6mm~152mm 33x optical zoom
WDR(140dB), Dual IR Cut Filter, 3D-DNR, HLC, BLC
Smart Defog, ROI
Support Auto Tracking
VCA (Tripwire/Double Tripwire/Perimeter/Object
Abandon/Object Lost/Running/Loitering/Parking/
Audio Abnormal/Video Abnormal/Heatmap/People
Counting)
Support Face Capture
Up to 500 presets,16 Cruise,8 pattern
8/2 Alarm in/out, 1/1 Audio in/out
Micro SD card 256GB
Smart IR, IR Range: 200m
IP67, PoE++



Call

Starlight **TC-H326S-Lite Spec:33X/I/E**

2MP 33x Starlight IR POE PTZ Camera
1/2.8" 2Megapixel Sony CMOS
Min. illumination Color: 0.002Lux@F1.5
S+265/H.265/H.264/MJPEG Triple-streams encoding
Up to 1920X1080@30fps
4.6mm~152mm 33x optical zoom
WDR(140dB), Dual IR Cut Filter, 3D-DNR, HLC, BLC
Smart Defog, ROI
VCA (Tripwire/Double Tripwire/Perimeter/Object
Abandon/Object Lost/Running/Audio Abnormal/
Video Abnormal)
Support Face Capture
Up to 500 presets,16 Cruise,8 pattern
1/1 Alarm in/out, 1/1 Audio in/out
Micro SD card 256GB
Smart IR, IR Range: 150m
IP67, PoE



169.000.000

Starlight **TC-H324S-Lite Spec: 25X/I/E/V**

2MP 25x Starlight IR PTZ Camera
1/2.8" 2Megapixel Sony CMOS
Up to 1920X1080@30fps
Min. illumination Color: 0.001Lux@F1.5
S+265/H.265/H.264/MJPEG Triple-streams encoding
4.8mm~120mm 25x optical zoom
WDR(140dB), Dual IR Cut Filter, 3D-DNR, HLC, BLC
Smart Defog, ROI
VCA (Tripwire/Double Tripwire/Perimeter/Object
Abandon/Object Lost/Running/Loitering/Parking/
Audio Abnormal/Video Abnormal/Heatmap/People
Counting)
Support Face Capture
500 presets,16 Cruise (32 preset per cruise),8 pattern
1/1 Alarm in/out, 1/1 Audio in/out
Micro SD card 256GB
Built-in Heater
IR Distance up to 150m
IP66, PoE



Call

Starlight **TC-H324S-Lite Spec: 25X/I/E**

2MP 25x Starlight IR PTZ Camera
1/2.8" 2Megapixel Sony CMOS
Up to 1920X1080@30fps
Min. illumination Color: 0.001Lux@F1.5
S+265/H.265/H.264/MJPEG Triple-streams encoding
4.8mm~120mm 25x optical zoom
WDR(140dB), Dual IR Cut Filter, 3D-DNR, HLC, BLC
Smart Defog, ROI
VCA (Tripwire/Double Tripwire/Perimeter/Object
Abandon/Object Lost/Running/Loitering/Parking/
Audio Abnormal/Video Abnormal/Heatmap)
500 presets,16 Cruise (32 preset per cruise),8 pattern
1/1 Alarm in/out, 1/1 Audio in/out
Micro SD card 256GB
Reset Button
IR Distance up to 150m
IP66, PoE



97.000.000



TC-R3105 Spec: I/B/V2.0

5CH 1HDD 1U NVR
5 IP camera input + 2 CH expansion = 7CH
S+265/H.265/H.264 video formats
Max 50/40 Mbps incoming/Outgoing bandwidth
Up to 6M Resolution Recording
Synchronous Decode: 1x6MP, 3x1080P
VCA detection alarm is supported
HDMI and VGA simultaneous output
HDMI Video output at up to 1080P (1920 × 1080)
1 SATA interface, up to 10TB for 1 HDD
1CH Audio output
2 USB Ports
1*10/100 Mbps Network Card
P2P support



18,600,000

TC-R3110 Spec: I/B/V2.0

10CH 1HDD 1U NVR
10 channel IP camera input
S+265/H.265/H.264 video formats
Max 50/40 Mbps incoming/Outgoing bandwidth
Up to 6MP Resolution Recording
Synchronous Decode: 1x6MP, 3x1080P
VCA detection alarm is supported
HDMI (2k)/VGA simultaneous video output
Support 1 SATA HDD up to 10TB
1CH Audio output
2 USB Ports
1*10/100 Mbps Network Card
P2P support



21,400,000

TC-R3210 Spec: I/F

10CH 2HDD 10ch Face Recognition NVR
10 IP camera input
S+265/H.265/H.264 video formats
Max 80/80 Mbps incoming/Outgoing bandwidth
Up to 6MP Resolution Recording
Synchronous Decode: 1x6MP, 3x1080P
Support Face Recognition: Face Picture Search/capturing pictures and typing in the library/encryption library management/face alarm information linkage
Base Libraries:32, Face pictures:10,000
Recognition with Face Capture camera: 5CH
Recognition with Normal camera: 1CH
VCA detection alarm is supported
HDMI and VGA simultaneous output(1080P)
2 SATA interfaces, up to 10TB for each HDD
Two-way Audio Input 1-ch
1CH Audio output
0/1 Alarm In/Out
2 USB Ports
1*10/100 Mbps Network Card
P2P support



Call

TC-R3120 Spec: I/B/V2.0

20CH 1HDD 1U NVR
20 channel IP camera input
S+265/H.265/H.264 video formats
Max 80/80 Mbps incoming/Outgoing bandwidth
Up to 8MP Resolution for Preview
Synchronous Decode: 1x4K, 4x1080P
VCA detection alarm is supported
HDMI(4K)/VGA simultaneous video output
Support 1 SATA HDD up to 10TB
1CH Audio output
2 USB Ports
1*10/100 Mbps Network Card
P2P support



27,500,000

TC-R3220 Spec: I/B/K

20CH 2HDD 1U NVR
20 channel IP camera input
S+265/H.265/H.264 video formats
Max 120/100 Mbps incoming/Outgoing bandwidth
Up to 8MP Resolution for Preview
Synchronous Decode: 1x4K, 4x1080P
VCA detection alarm is supported
HDMI and VGA simultaneous output
1*HDMI(4K)/1*VGA video output
Support 2 SATA HDD (10TB each SATA)
2*USB Ports
Two-way Audio Input 1-ch
1CH Audio output
4/1 Alarm In/Out
1*10/100 Mbps Network Card
P2P support



47.000.000



TC-R3240 Spec: I/B/N/H

40CH 4HDD 1.5U NVR
40 channel IP camera input
S+265/H.265/H.264 video formats
Max 320/320 Mbps incoming/Outgoing bandwidth
Up to 12MP Resolution for Preview
Synchronous Decode: 3x12MP, 4x4K, 16x1080P
VCA detection alarm is supported
HDMI and VGA independent outputs
1*HDMI(4K)/1*VGA video output
Support 2 SATA HDD (10TB each SATA)
2 USB Ports, 1*RS-485, 1*RS-232
Two-way Audio Input 1-ch
1CH Audio output
16/4 Alarm In/Out
2*10/100/1000 Mbps Network Card
P2P support



65.000.000

TC-R3216 Spec: I/B/X


16CH 2HDD 1.5U Hybrid NVR/XVR
Support HDTVI(8MP)/HDCVI(4MP)/AHD(5MP)/
IP(8MP)/CVBS Input
16Ch BNC or 32Ch IP Input
S+265/H.265/H.264 video formats
Max 128/128 Mbps incoming/Outgoing bandwidth
Up to 8MP Resolution for Preview
Synchronous Decode: 4x4K, 16x1080P
VCA detection alarm is supported
Support Face Detection, Auto tracking,
Demographics, Early Warning VCA
HDMI and VGA independent outputs
1*HDMI(4K)/1*VGA video output
Support 2 SATA HDD (10TB each SATA)
2 USB Ports, 1*RS-485, 1*RS-232
Two-way Audio Input 1-ch
1CH Audio output
16/4 Alarm In/Out
1*10/100/1000 Mbps Network Card
P2P support



99.500.000

TC-R3440 Spec: I/B/N

40CH 4HDD 1.5U NVR
40 channel IP camera input
S+265/H.264 video formats
Max 320/320 Mbps incoming/Outgoing bandwidth
Up to 12MP Resolution for Preview
Synchronous Decode: 3x12MP, 4x4K, 16x1080P
VCA detection alarm is supported
HDMI(4K)/VGA simultaneous video output
Support 4 SATA HDD (10TB each SATA)
2 USB Ports, 16/4 Alarm In/Out
2*RS-485, 1*RS-232
Two-way Audio Input 1-ch
1CH Audio output
16/4 Alarm In/Out
2*10/100/1000 Mbps Network Card
P2P support



Call

TC-R3440 Spec: I/B/N/H/C

40CH 4HDD 1.5U NVR
40 channel IP camera input
S+265/H.265/H.264 video formats
Max 200/200 Mbps incoming/Outgoing bandwidth
Up to 12MP Resolution for Preview
Synchronous Decode: 3x12MP, 4x4K, 16x1080P
VCA detection alarm is supported
HDMI and VGA independent outputs
1*HDMI(4K)/1*VGA video output
Support 4 SATA HDD(10TB each SATA)
2 USB Ports, 1*RS-485, 1*RS-232
Two-way Audio Input 1-ch
1CH Audio output
2*10/100/1000 Mbps Network Card
P2P support



Call

TC-R3840 I/B/N

40CH 8HDD 2U NVR
40 channel IP camera input
S+265/H.265/H.264 video formats
Max 320/320 Mbps incoming/Outgoing bandwidth
Max 12MP Resolution for Preview
Synchronous Decode: 2x12MP, 4x4K, 16x1080P
VCA detection alarm is supported
HDMI and VGA independent outputs
2*HDMI (4K)/2*VGA video output
Support N+M Hot Standby
Support ANR
8*SATA HDD up to 10TB for each HDD
1*e-SATA
Support Raid JBOD, RAID 0/1/5/6/10
3*USB Ports
Two-way Audio Input 1-ch
1x3.5mm, 1xBNC Audio output
16/4 Alarm In/Out
2*RS-485, 1*RS-232
2*10/100/1000 Mbps Network Card
P2P support



Call

TC-R3880 Spec: I/B/N

80CH 8HDD 2U NVR
80 channel IP camera input
S+265/H.265/H.264 video formats
Max 320/320 Mbps incoming/Outgoing bandwidth
Max 12MP Resolution for Preview
Synchronous Decode: 2x12MP, 4x4K, 16x1080P
VCA detection alarm is supported
HDMI and VGA independent outputs
2*HDMI(4K)/2*VGA video output
Support N+M Hot Standby
Support ANR
8*SATA HDD up to 10TB for each HDD
1*e-SATA
Support Raid JBOD, RAID 0/1/5/6/10
3*USB Ports
Two-way Audio Input 1-ch
1x3.5mm, 1xBNC Audio output
16/4 Alarm In/Out
2*RS-485, 1*RS-232
2*10/100/1000 Mbps Network Card
P2P support



Call

